250T/350T/500T Insulpour® Thermal Entrances Order Form JULY, 2020

EC 97913-058 ☐ LEED – Recycled Aluminum is required for this project.

Ship to:		Date of Order:		Billing Info/Quote #:
		P.O. #		Job Name:
Sold to:				
Cold to.		Request Date:		Contact Name:
		Request Date.		Contact Name.
1. Door Type: □ 250T □ 350T □ 500	0T	10. Flushbolts:		
2. Finish: Exterior #		·	☐ Prep only	·
Interior #		☐ Kawneer Std. ☐ Kawneer ◆ ☐ Others:		
3. Quantity: Interior RHO LHO Pair Out Pair Out		11. Door Holder / Stop (Custom Hardware):		
		☐ Prep & Provide ☐ Not Required ☐ Holder ☐ Stop ☐ Degree ☐		
			Concealed	Make/Model
req'dreq'dreq'd				
Exterior		12. Perimeter Framing: Required Not Required		
4. Door Opening: (4'0" x 9'0" Max. per leaf)		Options: Thermal (or)		Adapter (non-thermal)
Widthx Height		☐ 451T	□ 601T	☐ 1620 ☐ 7500
	Silicone	Type: ☐ Immediate (c	or) 🗆 Transc	om - Height =
6. Door Sweep:			107 Thormally	Broken (11/16" Std. BTM Clearance)
7. Top/Bottom Rails:		☐ Optional 6-3/4" Threshold	107 THEITHAIIY	Diokeii (11/10 Std. BTW Clearance)
Top Rails: Bottom Rails:		·		
□ 2-15/16" (250T) □ 3-7/8" (250T) only		□ No Threshold (11/16" Std. BTM Clearance) □ No Threshold Special BTM Clearance		
□ 3-1/2" (350T) □ 6-1/2" (250T / 350T / 500T □ 5" (500T) □ 7-1/2" (250T / 350T / 500T	′	14. Closers:		☐ Prep only ☐ Not Required
□ 2-15/16" (250T Deep Web) □ 10" (250T / 350T / 500T)	')	Provide		Li Flep Olly Li Not Nequiled
□ 3-11/16" (350T Deep Web) □ 12" (250T / 350T / 500T)		Concealed		<u>Surface</u>
□ 5" (500T Deep Web)		□ Calibre	☐ LCN 404	40 XP ☐ Falcon SC 60
8. Cross Rails:		☐ LCN 2030	☐ LCN 126	60 □ Norton 8100 BF (8100)
Number of Cross Rails Required: Not Required		☐ LCN 5030	□ Norton 1	601 ☐ Norton 8100 Cover
(If more than 2 Cross Rails, drawing must accompany order)		☐ International	H	lold Open: ☐ Yes ☐ No
Dimension is from bottom of door to top of Cross Rail				Degree of Open:
Write on lines provided location	of cross rail.	□ Oth	ier:	
□ 1-3/8" □ 2-1/4" ◆		Drop Plates:		
□ 3-1/2" ◆		□ Norton 037882 (1600)	☐ LCN 18	□ 4040 18
□ 6" ◆		☐ Norton 037883 PA (1600)	☐ LCN 180	G □ 4040 18G
□ 8-1/4" ◆		☐ Norton 037674 (8100)	☐ LCN 18F	PA 🔲 4040 18PA
Cross Rail "dim" does not include glass stops.		☐ Norton 037675 PA (8100)	☐ LCN 18 ⁻	ΓJ □ 4040 18TJ
	 	☐ Falcon 137824 PA	☐ LCN 126	60-18
Maximum (2) horizontal cross rails allowed. Vertical not available.			☐ LCN 126	60-PA
		15. Classic Push/Pull:	☐ Prep & P	rovide ☐ Prep only ☐ Not Required
	* *	☐ Style - CO-9/CP ☐	Style - CP-I	I.CP-II*
9. Hinging:		☐ Style - CO-9/CO-9 ☐	Style - CP/0	CP
☐ Offset Pivots (Std.) ☐ NRP Butt Hinges		☐ Style - CO-9		☐ Style - CO-12/CP
□ Power Transfer		☐ Style - CO-9/CP-II*		☐ Style - CO-12
☐ Electric Hinge Transfer		☐ Other		·
☐ Continuous Gear Hinge		* (CP-II push bars available as a custom order.)		
☐ Intermediate Required/ Per	r Leaf			
☐ Hinging by Others		☐ Custom Location:		

Hurricane Resistant





Laws and building and safety codes governing the design and use of Kawneer products, such as glazed entrance, window, and curtain wall products, vary widely. Kawneer does not control the selection of product configurations, operating hardware, or glazing materials, and assumes no responsibility therefor.

Kawneer reserves the right to change configuration without prior notice when deemed necessary for product improvement.
© 2018, Kawneer Company, Inc.

JULY, 2020			
EC 97913-058			

16. Locking: Hardware & Door Prep	☐ Frame Prep ☐ Not Required	
Mortise Lock	Concealed Exit Device	Rim Exit Device
☐ Standard Location	☐ Kawneer 1686 Conc. ◆ ☐ Kawneer 1686 MEL	☐ Kawneer 1786 Rim ☐ Kawneer 1786 MEL
□ Custom Location	☐ 1686 Lever ☐ Cylinder Dogging	☐ 1786 Lever ☐ Cylinder Dogging
☐ M.S. 1850 (Pair & Single)	☐ Falcon 1690 Conc. ☐ Falcon 1690 EL	☐ Falcon 1790 Rim ☐ Falcon 1790 EL
☐ M.S. 1850 - 020 ☐ M.S. 1850 - 050	☐ Falcon 1990 Conc.	☐ Falcon 2090 Rim
☐ M.S. 1890 (Pair & Single)	☐ A.R. 8400 Mortise (Single/Pairs - flushbolt required)	□ VD 99XP EO (500T)
☐ M.S. 2190* (Single Only)	☐ A.R. 8600 Conc.	□ VD 99XP w/110NL (500T)
☐ M.S. 4510 (Pair & Single)	□ VD 3347A EO	☐ CR ED5200S (500T)
☐ Cyl Ext. ☐ TTurn Int. ☐ Cyl Int.	□ VD 3347A w/388NL	☐ Removable Mullion ☐ RM Cylinder
☐ AR4565 Int.	□ VD 9947 EO (350T/500T Only)	☐ Exterior Cyl. Required
☐ Lever Ext./AR 4560 ☐ Lever Int.	□ VD 9947 w/110 NL. (350T/500T Only)	□ Others:
☐ Paddle/AR4590 Latch: ☐ Int. ☐ Ext.	☐ Falcon HH1690 ◆	
☐ Cyl Guard:	□ VD HH9947 EO ◆	
□ Exit Indicator	□ VD HH9947 w/110NL (350T/500T Only) ◆	
□ 2 Point Locking w/M.S. AR4015	☐ Exterior Cyl. Required	
□ 3 Point Locking w/M.S. (Pair Only) AR4085	□ Others:	
☐ 3 Point Locking includes M.S. ◆ (Pair & Single)		
□ Electric Strike (Pair & Single) AR7130		
Others:		
* (M.S. 2190 only available w/CO-12 push/pull combinations.)		
17. Comments / Tag#:		

