JANUARY, 2019	Versoleil™ SunShade	
EC 97913-049	Outrigger System Order Form	

20 0/0/0 0/0	VEDCOLEUTM			
	VERSOLEIL!™	OUTRIGGER QUOTE	REQUEST & ORDER E	NTRY FORM
CUSTOMER NAME				
CITY / STATE / ZIP				
JOB NAME				
DATE				
	ER NO			
UNIT	MARK			
	.EED – Recycled Aluminum is requ	ired for this project.		
	NOTE: PLEASE CHEC	K APPROPRIATE BOX OR BOXES	UNDER EACH HEADING BELOW	
PRODUCT	PRODUCT		ANCHOR BRACKET CLIP	
☐ 1600 WALL SYSTEM™	1	G Screw Spline	CURTAIN WALL STANDARD	ANCHOR
☐ 1600 WALL SYSTEM™	2 □ TRIFAB™ VG C	G Shear Block	☐ TRIFAB™ STANDARD ANCHO)R
☐ 1600UT SYSTEM™1			NONE (Manual Entry)	
☐ 1600 WALL SYSTEM™	5		ANGUAD DRAGKET AGUNT	
☐ 1600 SS ☐ 1600 SS SSG			ANCHOR BRACKET COUNT	Quantity Per Row
☐ 1630 SS IR				
_ 1000 00 111				
	*Sunshade Span	Spacing = C/L Vertical to C/L Vertical	ıl at Fascia Surface	
	☐ Left Span [Center Span	☐ Right Span	П
		T Contain Opani	I Night Opan	
			_	_
	Left Span Length	Center Span Length	Right Span Length	
	inches	inches	inches	
		Quantity of Center Span		
CORNERS Corner Count - Single Mu	llion	CORI	<u>NERS</u> er Count - Double Mullion	
90 Degree Outside Cor			0 Degree Outside Corner	Quantity
☐ 90 Degree Inside come			0 Degree Inside comer	Quantity Quantity
☐ 135 Degree Outside Co	-		35 Degree Outside Corner	Quantity
☐ 135 Degree Inside corn			35 Degree Inside corner	Quantity
Number of Rows on Elevation	on			
ADDITIONAL INFORMA	ATION OR SKETCH:			



STANDARD OUTRIGGERS	STANDARD FASCIAS	STANDARD BLADES	
30" SQUARE	RECTANGULAR	☐ INFINITY	☐ FLARE
36" SQUARE		☐ ARCH	○ □ CIRCULAR
30" ROUNDED	☐ BULLNOSE	☐ AIRFOIL	□ diamond
36" ROUNDED □		☐ PLANAR	☐ SQUARE
		□ wave	
30" WEDGE	☐ ANGULAR	○ □ circular	
36" WEDGE			
30" CURVED	☐ CIRCULAR	○ □ circular	☐ SQUARE
36" CURVED		€ □ DIAMOND	

